

Flachkopfschrauben mit Innensechskant

Gewinde: metr. ISO-Gewinde, Regelgewinde nach DIN 13

Hexagon socket button head screws

Thread: metric ISO-thread, coarse pitch acc. to DIN 13

ISO 7380-1 010.9

L / Ø	M3	M4	M5	M6	M8	M10	M12
4							
5							
6							
8							
10							
12							
16							
20							
25							
30							
35							
40							
45							
50							
55							
60							
65							
70							
75							
80							

■ 010.9 plain / zinc plated
 ■ 010.9 black zinc plated
 ■ 010.9 six lobes drive



classic

LAGER · STOCK

ISO 7380-2 010.9 (mit Flansch / with flange)

L / Ø	M3	M4	M5	M6	M8	M10	M12
5							
6							
8							
10							
12							
16							
20							
25							
30							
35							
40							
45							
50							
55							
60							
65							
70							

■ 010.9 plain / zinc plated
 ■ 010.9 black zinc plated

Innensechskantschrauben mit niedrigem Kopf und Schlüsselführung

Gewinde: metr. ISO-Gewinde, Regelgewinde nach DIN 13

Low head socket cap screws with centre hole

Thread: metric ISO-thread, coarse pitch acc. to DIN 13

DIN 6912 08.8

L / Ø	M4	M5	M6	M8	M10	M12	M16	M20
8								
10								
12								
16								
20								
25								
30								
35								
40								
45								
50								
55								
60								
65								
70								
75								
80								
85								
90								
95								
100								

■ 08.8 plain / zinc plated

