

Sechskantschrauben mit Schaff

Gewinde: metr. ISO-Gewinde, Regelgewinde nach DIN 13

Hexagon head bolts

Thread: metric ISO-thread, coarse pitch acc. to DIN 13

ISO 4014

8.8 10.9

L/Ø	M10	M12	M14
40	8.8	10.9	
45	8.8	10.9	
50	8.8	10.9	
55	8.8	10.9	
60	8.8	10.9	
65	8.8	10.9	
70	8.8	10.9	
75	8.8	10.9	
80	8.8	10.9	
85	8.8	10.9	
90	8.8	10.9	
95	8.8	10.9	
100	8.8	10.9	
110	8.8	10.9	
120	8.8	10.9	
130	8.8		
140	8.8		
150	8.8		
160	8.8		
170	8.8		
180	8.8		
190	8.8		
200	8.8		
210	8.8		
220	8.8		

8.8 plain / zinc plated
10.9 plain

Sechskantschrauben mit Gewinde bis Kopf

Gewinde: metr. ISO-Gewinde, Regelgewinde nach DIN 13

Hexagon head screws

Thread: metric ISO-thread, coarse pitch acc. to DIN 13

ISO 4017

8.8 10.9

L/Ø	M10	M12	M14
16	8.8		
20	8.8		
25	8.8	10.9	
30	8.8	10.9	
35	8.8	10.9	
40	8.8	10.9	
45	8.8	10.9	
50	8.8	10.9	
55	8.8	10.9	
60	8.8	10.9	
65	8.8	10.9	
70	8.8	10.9	
75	8.8	10.9	
80	8.8	10.9	
85	8.8	10.9	
90	8.8	10.9	
95	8.8	10.9	
100	8.8	10.9	
110	8.8	10.9	
120	8.8	10.9	
130	8.8	10.9	
140	8.8	10.9	
150	8.8	10.9	
160	8.8	10.9	

